



1999-2004 Jeep Grand Cherokee Headlight Bulb Replacement

Burned out headlight on the driver side. Passenger side removes the same way.

Written By: oldturkey03



INTRODUCTION

Here is a straight forward bulb replacement. Only requires the simplest of tools and is a quick fix.



TOOLS:

- [7mm Wrench](#) (1)
- [Flathead Screwdriver](#) (1)



PARTS:

- [Replacement Bulb](#) (1)
9006XS

Step 1 — Headlight Bulb



- Here is a 2000 Jeep Grand Cherokee with a burned out driver side headlight bulb.
- Open the hood. On top of the affected headlight assembly is a single 7mm hex bolt.
- Remove the bolt

Step 2



- Remove the bolt. It is approximately 6 inches long.
- Grab the headlight assembly on the fender side,
- as well as the grill side.

Step 3



- Then pull the assembly straight out
- The light bulbs will now be accessible.
- Remove the bulb by twisting it in a counter clockwise direction, then pulling it out of the headlight assembly.

Step 4



- Use a flathead screwdriver (or similar tool) to lift the socket clip of the tab on the bulb and remove the bulb.
- Change the bulb and the result will be fully functional headlights.

To reassemble your headlight, follow these instructions in reverse order.

This document was last generated on 2017-06-30 03:49:10 AM.